



CM ALMY

ALMY LIQUID CANDLE RACK ASSEMBLY INSTRUCTIONS

Contents

- 1 Rack Top
- 1 Rack Base
- 2 Rack Sides
- 1 Brass Handle
- 2 handle screws (silver colored)
- 8 assembly screws (brass colored with wood screw thread)
- 1 Allen wrench
- 4 self adhesive urethane pads

Step 1: Attach brass handle to rack top

- A** Identify the top side of the rack top. The rack top has holes drilled completely through the wood panel. The “top side” of the rack top has smoother, more contoured edge on the larger holes for the candles to drop through. There are two smaller holes in the center of the top for the handle screws.
- B** Fasten handle to top side of rack top. Align the handle with the small holes. Use either a Phillips head or a slot head screwdriver to fasten the silver colored screws into the handle.

Step 2: Fasten the top and bottom to the sides

- A** Screw rack bottom onto sides. Identify the rack bottom — it has one surface with candle holder holes drilled partially through. Side pieces should rise from this surface. Align the rack bottom’s small holes with those on at one end of a side piece. Use your fingers to start screws. Repeat on the opposite side. Once all four screws are started use the Allen wrench to tighten the screws.
- B** Screw rack top onto sides. Place the rack bottom on a work surface with the sides facing up. Align the rack top’s screw holes with those on the sides. Be sure the handle is up. Start all four assembly screws with your fingers and then tighten with the Allen wrench.

Step 3: Affix bottom pads

- A** Make sure the bottom surface of the rack is clean and dry.
- B** Peel the urethane bottom pads from their paper one at a time and position on each corner pressing firmly in place.

800.225.2569 www.almy.com



AIK303-1

AS303-1